



CHARACTERISTICS

- Cleaning product
- Solvent based cleaner
- Perfect adhesion of oxime-based sealants on lacquered metals

APPLICATIONS

- For removing dirt and grease on all metals lacquered, non lacquered, relief lacquers and several plastics.
- Has to be used before **Parasilico AM85-1** or any other sealant on oxime base, will be applied.

TECHNICAL CHARACTERISTICS	
Physical state	Liquid
Colour	Colourless/ Transparent
Odour	Characteristic
Density (20°C)	0,86 g/ml
Shelf life, in the original packing in dry conditions between +5°C - +25°C	2 years

PACKING
15 cans of 500 ml/box - 48 boxes/pallet
Can 5 l - 120 cans/pallet
Jar 25 l - 26 jars/pallet

METHOD OF USE

Application

- Clean the surface with a wet cloth.
- Wait until the surface is dry (depending the circumstances, it takes 5 minutes).
- Afterwards the sealant can be applied.

SAFETY

Safety data sheet available on request

LIMITATIONS

- Some lacquers can be affected. It is recommended to test the compatibility with the paint in advance.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply.