



## CHARACTERISTICS

- Cleansing product
- Degreaser
- Transparent liquid
- Does not contain any antistaticum

## APPLICATIONS

- Suitable for removing non-cured sealant
- As well as cleaning and degreasing of several surfaces
- Remark: On lacquered and anodized aluminium: before use, preliminary tests are necessary.

TECHNICAL CHARACTERISTICS	
Fysical condition (20°C)	Liquid
Colour	Colourless
Odour	Typical
Boiling interval	78-113°C
Ignition point (CC)	9°C
Self-ignition temperature	> 200°C
Density (15°C)	0,72 g/cc
Shelf life, in the original packing in dry conditions between +5°C - +25°C	2 years

PACKING
12 spray cans of 400 ml/box - 60 boxes/pallet
Jar 5 l - 120 jars/pallet
Jar 25 l - 26 jars/pallet
Barrel 200 l - 2 barrels/pallet - On demand

## METHOD OF USE

### Preparation

We recommend, before use, to check if the product is convenient for its application and to do some preliminary tests.

### Removing of fresh, non cured sealant:

Remove as much as possible beforehand with a cloth or cleaning paper. Follow instructions below:

Aerosol 400 ml:

- Shake aerosol before use
- Spray from a distance on the surface or on the non cured sealant
- Then rub the surface with a clean cloth

Jerry can 5 l - 25 l

- Soak a cloth with **Parasilico Cleaner** and remove the remaining sealant
- Then rub the surface with a clean cloth

### Cleaning and degreasing of surfaces

Aerosol 400 ml:

- Shake aerosol before use
- Spray from a distance on the surface
- Rub the surface in order to clean with a clean cloth or paper
- Renew the cleaning paper regularly

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply.

Jerry can 5 l & 25 l:

- Moisten a cloth or cleaning paper with **Parasilico Cleaner**
- Clean and degrease the surface by rubbing it
- Renew the cleaning paper regularly

## **SAFETY**

Safety data sheet available on request.

## **LIMITATIONS**

On lacquered and anodized aluminium: before use, preliminary tests are necessary.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply.