

## CE Declaration of Performance (DoP)

N° MP0060028

In accordance with annex III of the EU regulation 305/2011

1. Unique identification code of the product type:

**PARACRYL STANDARD**

2. Type, batch or serial number, or any other element allowing identification of the construction product as required pursuant to article 11 (4):

**Batch number: See entry on packaging**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**Sealant for facade application interior – Conform EN 15651-1:2012 Type F INT Class 7,5 P**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to article 11 (5):

**DL CHEMICALS  
Roterijstraat 201-203  
BE-8793 Waregem**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in article 12 (2):

**Not applicable**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in annex V:

**System 4**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**The determination of the product type based on type testing under system 4 is the sole responsibility of the manufacturer**

8. In case of the declaration of performance concerning a construction product of which a European Technical Assessment has been issued:

**Not applicable**

## CE Declaration of Performance (DoP)

N° MP0060028

In accordance with annex III of the EU regulation 305/2011

9. Declared performances:

Essential characteristics – Type F INT	Performance	Technical harmonised specification
Reaction to fire (classification according EN 13501-1:2007)	Class E	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	
Water and air tightness		
Resistance to flow (according EN ISO 7390)	≤ 5 mm	
Loss of volume (according EN ISO 10563)	≤ 45%	
Tensile properties <ul style="list-style-type: none"> <li>At maintained extension after water immersion (according EN ISO 10590)</li> </ul>	≥ 25%	
Durability	Pass	
Conditioning : Method A Substrate : Façade : Anodized Aluminium + M2 Concrete		

10. The performance of the product identified in points 1 & 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified under point 4.

Signed for and on behalf of the manufacturer by:



Joris Van Hoey  
 Quality Control Manager

Waregem – November 2022

## CE marking

N° MP0060028

In accordance with annex III of the EU regulation 305/2011



22

DL CHEMICALS

Roterijstraat 201-203 BE-8793 Waregem, België

### PARACRYL STANDARD

DoP No. MP0060028

EN 15651-1:2012

Sealant for facade application interior – Type F INT Class 7,5 P

Essential characteristics	Performance	Technical harmonised specification
Reaction to fire	Class E	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	
Water and air tightness		
Resistance to flow	≤ 5 mm	
Loss of volume	≤ 45%	
Tensile properties <ul style="list-style-type: none"> <li>At maintained extension after water immersion</li> </ul>	≥ 25%	
Durability	Pass	
Conditioning: Method A Substrate Façade: Anodized Aluminium + M2 Concrete		
<a href="https://www.dl-chem.com/en/dop">https://www.dl-chem.com/en/dop</a>		

## UKCA Declaration of Performance (DoP)

N° MP0060028

In accordance with annex III of the EU regulation 305/2011

1. Unique identification code of the product type:

**PARACRYL STANDARD**

2. Type, batch or serial number, or any other element allowing identification of the construction product as required pursuant to article 11 (4):

**Batch number: See entry on packaging**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**Sealant for facade application interior – Conform EN 15651-1:2012 Type F INT Class 7,5 P**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to article 11 (5):

**DL CHEMICALS  
Roterijstraat 201-203  
BE-8793 Waregem**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in article 12 (2):

**Not applicable**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in annex V:

**System 4**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**The determination of the product type based on type testing under system 4 is the sole responsibility of the manufacturer**

8. In case of the declaration of performance concerning a construction product of which a European Technical Assessment has been issued:

**Not applicable**

## UKCA Declaration of Performance (DoP)

N° MP0060028

In accordance with annex III of the EU regulation 305/2011

9. Declared performances:

Essential characteristics – Type F INT	Performance	Technical harmonised specification
Reaction to fire (classification according EN 13501-1:2007)	Class E	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	
Water and air tightness		
Resistance to flow (according EN ISO 7390)	≤ 5 mm	
Loss of volume (according EN ISO 10563)	≤ 45 %	
Tensile properties <ul style="list-style-type: none"> <li>At maintained extension after water immersion (according EN ISO 10590)</li> </ul>	≥ 25 %	
Durability	Pass	
Conditioning : Method A Substrate : Façade : Anodized Aluminium + M2 Concrete		

10. The performance of the product identified in points 1 & 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified under point 4.

Signed for and on behalf of the manufacturer by:



Joris Van Hoey  
 Quality Control Manager

Waregem – November 2022

## UKCA marking

N° MP0060028

In accordance with annex III of the EU regulation 305/2011

# UK CA

22

DL CHEMICALS  
 Roterijstraat 201-203 BE-8793 Waregem, België

### PARACRYL STANDARD

DoP No. MP0060028

EN 15651-1:2012

Approved Body 1234

Sealant for facade application interior – Type F INT Class 7,5 P

Essential characteristics	Performance	Technical harmonised specification
Reaction to fire	Class E	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	
Water and air tightness		
Resistance to flow	≤ 5 mm	
Loss of volume	≤ 45%	
Tensile properties <ul style="list-style-type: none"> <li>At maintained extension after water immersion</li> </ul>	≥ 25%	
Durability	Pass	
Conditioning: Method A Substrate Façade: Anodized Aluminium + M2 Concrete		
<a href="https://www.dl-chem.com/en/dop">https://www.dl-chem.com/en/dop</a>		