

Declaration of performance

Majvest 700 SOB 8975-150033 - Vers.2.0

Nr. DoP-20-897-33

1. Unique identification code of the product-type

8975-150033

2. Product labeling

Majvest 700 SOB

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer

Facade membrane
Flexible sheets for waterproofing - Underlays for walls - EN 13859-2:2014

4. Name and contact address of the manufacturer

SIGA Cover AG
Rüt mattstrasse 7
6017 Ruswil
Switzerland

5. Name of the authorized representative whose mandate covers the tasks specified in Article 12, Paragraph 2

-

6. System of assessment and verification of constancy of performance of the construction product

AVCP System 3

7. Notified body

Laboratoire National de métrologie et d'Essais (LNE)
NB 0071
SGS INTRON CERTIFICATIE B.V.
NB 0958
Has carried out the assessment and verification according to system "3" and issued a test reports

8. Declared Performance

Essential characteristics	Performance	Bottom tolerance	Top tolerance	Unit	Test Standard EN 13859-2:2014
Length	33.4	33.2	33.7	m	EN 1848-2
Width	1500	1492	1508	mm	EN 1848-2
Mass per unit area	270	240	300	g/m ²	EN 1849-2
Reaction to fire	B-s1, d0			class	EN 13501-1
Resistance to water penetration	W1			class	EN 1928
Water vapour transmission Sd-Value	0.01	0.01	0.06	m	EN 12572
Tensile property max. force (MD)	350	320	450	N/50mm	EN 12311-1
Tensile property max. force (CD)	270	230	350	N/50mm	EN 12311-1
Tensile property elongation (MD)	35	20	60	%	EN 12311-1

Tensile property elongation (CD)	40	20	60	%	EN 12311-1
Resistance to tearing (nail tearing) (MD)	140	100	250	N	EN 12310-1
Resistance to tearing (nail tearing) (CD)	140	100	250	N	EN 12310-1
Flexibility at low temperatures	-40			°C	EN 1109
Tensile property max. force (MD) after artificial ageing	300	240	360	N/50mm	EN 13859-1 Anh. C EN 12311-1
Tensile property max. force (CD) after artificial ageing	220	176	264	N/50mm	EN 13859-1 Anh. C EN 12311-1
Tensile property elongation (MD) after artificial ageing	27	15	40	%	EN 13859-1 Anh. C EN 12311-1
Tensile property elongation (CD) after artificial ageing	27	15	40	%	EN 13859-1 Anh. C EN 12311-1
Resistance to water penetration after artificial ageing	W1			class	EN 13859-1 Anh. C EN 1928
Hazardous substances	none				

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance (DOP) is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom, under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Seline Zürcher – Quality Management



Ruswil, 07.12.2022