



CHARACTERISTICS

- Joint and adhesive sealant
- Permanent elasticity
- Excellent adhesion to almost all building materials
- High resistance to UV
- Can be applied to dry and slightly damp surfaces
- Excellent flexibility
- High resistance to ageing and weather conditions
- Also adheres under water

APPLICATIONS

- Waterproof finishing of complex roof details such as domes, upstands, skylights, chimneys, ventilation pipes, gutters, etc.
- Plugging cracks, fissures and blisters in roofs and gutters.
- Sealing leaks and emergency repairs during rainy weather.
- Bonding to bituminous surfaces, roofing, roof rolls, tiles, insulation boards, etc.
- Waterproof sealing of joints, seams, and roof edge closures

TECHNICAL CHARACTERISTICS

Type of product	Bitumen, SBS elastomers and resin
Density (g/ml)	1.21
Consistency	Pasta
Curing time	12 hours
Application temperature	+5°C - +30°C
Temperature resistance	-20°C - +80°C
Consistence: ISO 7390	Non-existent
Shelf life of unopened product	36 months
Storage conditions	Store in a dry, cool place at +5°C to +25°C. Keep out of direct sunlight.

PACKING AND COLOURS

12 x cartridge 300ML/box - 1200 pieces/pallet

Black

20 x foil bag 600ML/box - 900 pieces/pallet

Black

METHOD OF USE

Preparation

- Use in well-ventilated rooms. Good ventilation is important during application and curing of the product.
- The surface must be solid, strong enough and clean, dust and fat-free.
- If needed degrease the materials to be glued with Parasilico Cleaner, MEK, fire alcohol, ethanol.
- The user needs to make sure that the product is suitable for the application. Consult our technical service if necessary.
- It is recommended to carry out tests on every surface before use.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply

Application

- Apply the product from the cartridge or foil packaging with a manual or pneumatic caulking gun.
- After application, there is almost immediately sufficient adhesive strength to withstand a small load. Maximum adhesive strength after complete drying.

Consumption

300 ml/m²

Cleaning

- Clean tools with white spirit.

SAFETY

Consult the safety information on the packaging and the safety data sheet for more information.

POINTS OF ATTENTION

- Not suitable for use on natural stone (can cause stains).
- Not suitable for use on EPDM.
- Not appropriate for use on polystyrene (XPS, EPS).
- Not suitable for use on insulation boards that are not resistant to solvents

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply