



CHARACTERISTICS

- Construction adhesive
- No nails or screws needed
- Immediate adhesion
- Filling capacity
- Very high traction adhesive
- Waterbased, solvent free and odourless

APPLICATIONS

- For assembling and sealing elements in polystyrene or expanded polyurethane.
- Also suitable for bonding on concrete, masonry, plaster, wood, metal, PVC, etc.

TECHNICAL CHARACTERISTICS	
Base	Acrylic (synthetically elastomere)-emulsion
Traction resistance after drying	45 kg/cm ²
Density	1,65 kg/l
Open time	13 - 18 min.
VOC	< 50 g/l
Shelf life, in the original packing in dry conditions between +5°C-+25°C	15 months
Temperature resistance	-25°C - +70°C

PACKING AND COLOUR
25 cartridges of 310 ml/box - 48 boxes/pallet
White

METHOD OF USE

Preparation

The surfaces must be clean, dry, sound and free of dust.

Application

- Apply in bands or in plots on the material or substrate.
- Compress the material to be glued into the correct position.
- Repositioning is possible for 30 minutes.
- Heavy materials exceeding 8 kg/m² must be supported for 8 to 15 hours.
- A good adhesion is obtained after 1 hour but wait at least 24 to 48 hours before submitting the supports to traction.

Cleaning

With water.

TECHNICAL APPROVALS



* Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply.