



CHARACTERISTICS

- Adhesive based on neoprene
- Gap filling: possible to bond materials to uneven surfaces (up to 8 mm)
- High bond strength and adhesion
- No nails & screws
- Can be overpainted in certain circumstances.

APPLICATIONS

- Specially developed to give high bond strength and adhesion to most common building materials without the use of mechanical fixings such as nails
- Ideal for use both inside and outside and both porous and non porous surfaces
- Horizontally and vertically
- Gluing skirting boards, mouldings, window sills, sheeting, name plates, hooks and decorative ornaments.

TECHNICAL CHARACTERISTICS	
Solid contents	60%
Viscosity	Paste
Density	1,22 g/ml
Colour	Beige
Tensile force wood/wood	20°C : 60 kg/cm ²
Water absorption	Nil
Application temperature	+10°C - +40°C
Shelf life, in the original packing in dry conditions between +5°C - +25°C	Min. 12 months
Skin forming	5 min.
Inflammable	Yes
Processing time	5 - 20 min.
Temperature resistance	-20°C - +100°C

PACKING AND COLOURS
25 cartridges of 310 ml/box - 48 boxes/pallet
Beige

METHOD OF USE

Preparation

- All surfaces should be clean and dry.

Application

- Must be applied in cords of min. 5 mm diameter and with a max. of 10 cm between the parallel lines.
- Press on the other surface, take off, wait a few minutes to let the vapours escape (5 min). This drying time can be extended to 30 minutes.
- Apply again and press hard (Transfer method). The object has to be positioned with great precision, as the setting is almost immediate.
- Final adherence is reached in 12 hours.
- Where heavier items are being fixed, support them while the adhesive is drying to eliminate any possible slippage.

Consumption

1 cordon of 5 mm width covers approx. 15 meters per cartridge

Baseboards < 7 cm in width: 1 line of glue

Baseboards > 7 cm in width: 2 lines of glue.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply.

Cleaning

With toluene

SAFETY

Safety data sheet available on request.

LIMITATIONS

- Should not be used in areas where it may be totally be immersed in water.
- Not to be used on polystyrene foam and synthetic surfaces.

TECHNICAL APPROVALS



* Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply.