



## CHARACTERISTICS

- Polyurethane sealant
- Ready-to-use
- Solvent-based
- Primer based on solvents and polyurethane
- Promotes adhesion of polyurethane sealants and hybrid polymer sealants and MS
- Reduces or even avoids blistering generated by curing in difficult conditions on porous materials such as concrete or wood

## APPLICATIONS

- For both absorbent and non-absorbent surfaces.
- Can also be used to prevent migration of plasticizers

## TECHNICAL CHARACTERISTICS

Type of product	Polyurethane solution
Drying time (depending on the layer thickness and atmospheric conditions)	10 - 15 minutes
Application temperature	+5°C - +35°C
Viscosity (mPa.s, Brookfield)	50
Shelf life of unopened product	12 months
Storage conditions	Store in a dry, cool place at +15°C to +25°C.
Shelf life after opening	1 month

## PACKING AND COLOURS

**12 x can 250ML/box - 1080 pieces/pallet**

Transparent, Black

**8 x can 1L/box - 288 pieces/pallet**

Transparent, Black

## METHOD OF USE

### Preparation

- The surfaces must be solid, dry and free of dust and grease.
- If needed degrease the materials to be glued with Parasilico Cleaner, MEK, fire alcohol, ethanol.
- It is recommended to carry out tests on every surface before use.
- Shake vigorously before use.

### Application

- Apply primer with a brush in a thin, even and homogeneous layer. Avoid thick layers as this will reduce adhesion.
- For porous substrates it is necessary to apply the primer in two layers.
- After the drying time of 15 minutes, the sealant/adhesive must be applied as soon as possible (within 60 minutes).

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply

- Close the bottle after use because the primer is sensitive to air moisture. After opening the bottle, use the product within 1 month.

### **Cleaning**

- Clean with White Spirit within the first 5 minutes. After that time, cleaning with MEK is required.

### **SAFETY**

Consult the safety information on the packaging and the safety data sheet for more information.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply