

**CHARACTERISTICS**

- One component glue
- Ready-to-use
- Very easy to apply
- Water-based
- Peel resistant
- Solvent free
- Adheres powerfully and quickly
- Short waiting time
- Very low emission

APPLICATIONS

- Bonding of flexible floor coverings for indoor applications, such as cushion vinyl, linoleum and many types of carpet with common backing
- Bonding of cork and homogeneous and heterogeneous PVC floor coverings in sheets and tiles
- Suitable for use on floors with underfloor heating and floor cooling (reversible system)

TECHNICAL CHARACTERISTICS

Type of product	Acrylic dispersion
Density (g/ml)	1.62
Consistency	Pasta
Temperature of the surface	+15°C
Application temperature	+15°C - +25°C
Chargeable after	24 h
Waiting time	10 - 15 minutes
Working time at 23 degrees C and 50% R.H.	30 minutes
Shelf life of unopened product	15 months
Storage conditions	Store in a dry, cool place at +5°C to +25°C. Keep out of direct sunlight.

PACKING AND COLOURS

bucket 15kg - 33 pieces/pallet
Chalk white

METHOD OF USE**Preparation**

- The surface should be permanently dry, completely level, clean and free from dust, paint, loose parts.... and must retain its pressure and form. Check whether surface complies with the applicable norms and technical regulations.
- If necessary, apply a levelling layer (DL Egaline) at least 2 mm thick, especially on non-absorbent substrates in combination with floor coverings with a closed backing.
- The floor covering must be sufficiently acclimatised and relaxed before bonding.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply

Application

- For hot-water underfloor heating, the system must be switched off at least 72 hours before application. Do not switch the underfloor heating back on until 3 days after the floor has been fully finished.
- Apply the adhesive evenly to the substrate using a suitable notched trowel (see consumption table) at an angle of 60°.
- Lay the floor covering after a short waiting time of 10 minutes and within the open time of 30 minutes.
- After laying, press the floor covering firmly over the entire surface so that the adhesive is evenly distributed on the backing and no air is trapped. Weight down or roll end edges, uneven seams and deformations.
- 20 minutes after laying, press the entire floor covering down again, especially at the seams and edges.

Consumption

Floor covering with solid back A2 +- 300 - 350 g/m²

Floor covering with uneven back B1 +- 400 - 450 g/m²

Floor covering with rough back B2 +- 600- 650 g/m²

Cleaning

- Clean uncured residues with water
- Cured product can only be removed mechanically.

SAFETY

Consult the safety information on the packaging and the safety data sheet for more information.

POINTS OF ATTENTION

- Do not apply to surfaces that are not protected against any rising moisture. If necessary, apply a moisture barrier (Hydroblocker 3K).
- Waiting time and open time depend on several factors. The times are shorter at higher temperatures, lower humidity. The times are longer at lower temperatures, higher humidity and low suction surfaces
- Not suitable for LVT.
- Not suitable for damp areas or continuous water exposure.

TECHNICAL APPROVALS AND QUALITY LABELS

- French VOC emission class A+



This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply